



UNIVERSITY COLLEGE LONDON

DEPARTMENT OF ELECTRONIC AND ELECTRICAL ENGINEERING

Performance characterisation of 8-bit RISC and OISC architectures

<i>Author:</i>	<i>Supervisor:</i>	<i>Second Assessor:</i>
Mindaugas	Prof. Robert	Dr. Ed
JARMOLOVIČIUS	KILLEY	ROMANS
zceemja@ucl.ac.uk	r.killey@ucl.ac.uk	e.romans@ucl.ac.uk

A BEng Project Final Report

March 27, 2020

destinations. Final design has **15** destination and **41** source addresses. This is not the most space efficient design as 41 source addresses would require only six bits for address, wasting two bits every time non-immediate source is used.

Full list of OISC sources and destinations are listed in table ?? in Appendix section.

5.2 Immediate values

5.3 Arithmetic Logic Unit

5.4 Memory

6 Results and Analysis

7 Conclusion

8 References

9 Appendix

Table 1: Instruction set for RISC processor. * Required immediate size in bytes

Instr.	Description	I-size *
<i>2 register instructions</i>		
MOVE	Copy value from one register to other	0
ADD	Arithmetical addition	0
SUB	Arithmetical subtraction	0
AND	Logical AND	0
OR	Logical OR	0
XOR	Logical XOR	0
MUL	Arithmetical multiplication	0
DIV	Arithmetical division (inc. modulus)	0
<i>1 register instructions</i>		
COPY0	Copy intimate to a register 0	1
COPY1	Copy intimate to a register 1	1
COPY2	Copy intimate to a register 2	1
COPY3	Copy intimate to a register 3	1
ADDC	Arithmetical addition with carry bit	0
ADDI	Arithmetical addition with immediate	1
SUBC	Arithmetical subtraction with carry bit	0
SUBI	Arithmetical subtraction with immediate	1
ANDI	Logical AND with immediate	1
ORI	Logical OR with immediate	1
XORI	Logical XOR with immediate	1
CI0	Replace intimate value byte 0 for next instruction	1
CI1	Replace intimate value byte 1 for next instruction	1
CI2	Replace intimate value byte 2 for next instruction	1
SLL	Shift left logical	1
SRL	Shift right logical	1
SRA	Shift right arithmetical	1
LWHI	Load word (high byte)	3
SWHI	Store word (high byte, reg. only)	0
LWLO	Load word (low byte)	3
SWLO	Store word (low byte, stores high byte reg.)	3
INC	Increase by 1	0
DEC	Decrease by 1	0
GETAH	Get ALU high byte reg. (only for MUL & DIV & ROL & ROR)	0
GETIF	Get interrupt flags	0
PUSH	Push to stack	0
POP	Pop from stack	0
COM	Send/Receive to/from com. block	1
BEQ	Branch on equal	3
BGT	Branch on greater than	3
BGE	Branch on greater equal than	3

Table 1: Instruction set for RISC processor. * Required immediate size in bytes

Instr.	Description	I-size *
BZ	Branch on zero	2
<i>0 register instructions</i>		
CALL	Call function, put return to stack	2
RET	Return from function	0
JUMP	Jump to address	2
RETI	Return from interrupt	0
INTRE	Set interrupt entry pointer	2

Table 2: Instructions for OISC processor.

Name	Description
<i>Destination Addresses</i>	
ACC0	Set ALU source A accumulator
ACC1	Set ALU source B accumulator
BR0	Set Branch pointer register (low byte)
BR1	Set Branch pointer register (high byte)
BRZ	If source value is 0, set program counter to branch pointer
STACK	Push value to stack
MEM0	Set Memory pointer register (low byte)
MEM1	Set Memory pointer register (middle byte)
MEM2	Set Memory pointer register (high byte)
MEMHI	Save high byte to memory at memory pointer
MEMLO	Save low byte to memory at memory pointer
COMA	Set communication block address register
COMD	Send value to communication block
REG0	Set general purpose register 0
REG1	set general purpose register 1
<i>Source Addresses</i>	
NULL	Get constant 0
ALU0	Get value at ALU source A accumulator
ALU1	Get value at ALU source B accumulator
ADD	Get Arithmetical addition of ALU sources
ADDC	Get Arithmetical addition carry
ADC	Get Arithmetical addition of ALU sources and carry
SUB	Get Arithmetical subtraction of ALU sources
SUBC	Get Arithmetical subtraction carry
SBC	Get Arithmetical subtraction of ALU sources and carry
AND	Get Logical AND of ALU sources
OR	Get Logical OR of ALU sources
XOR	Get Logical XOR of ALU sources
SLL	Get ALU source A shifted left by source B
SRL	Get ALU source A shifted right by source B
ROL	Get rolled off value from previous SLL instance
ROR	Get rolled off value from previous SRL instance
MULLO	Get Arithmetical multiplication of ALU sources (low byte)

Table 2: Instructions for OISC processor.

Name	Description
MULHI	Get Arithmetical multiplication of ALU sources (high byte)
DIV	Get Arithmetical division of ALU sources
MOD	Get Arithmetical modulus of ALU sources
EQ	Check if ALU source A is equal to source B
GT	Check if ALU source A is greater than source B
GE	Check if ALU source A is greater or equal to source B
NE	Check if ALU source A is not equal to source B
LT	Check if ALU source A is less than source B
LE	Check if ALU source A is less or equal to to source B
BR0	Get Branch pointer register value (low byte)
BR1	Get Branch pointer register value (high byte)
PC0	Get Program counter value (low byte)
PC1	Get Program counter value (high byte)
MEM0	Get Memory pointer register value (low byte)
MEM1	Get Memory pointer register value (middle byte)
MEM2	Get Memory pointer register value (high byte)
MEMHI	Load high byte from memory at memory pointer
MEMLO	Load low byte from memory at memory pointer
STACK	Pop value from stack
ST0	Get stack address value (low byte)
ST1	Get stack address value (high byte)
COMA	Get communication block address register value
COMD	Read value from communication block
REG0	Get value from general purpose register 0
REG1	Get value from general purpose register 1